

Blackhawk Trucker Edge Compact Lite

698 - 2100 MHz, 5dBi (ANT-BH-00030)

This premium grade antenna will satisfy 3G and 4G capabilities for all the major networks in Australia and can be used for commercial and industrial 3G and 4G applications. The Blackhawk Omni Trucker Edge Compact LITE at 60cm will provide the perfect solution for voice and data applications. It is lighter in weight than its sister antenna the Trucker Edge Compact, weighing only 1.2kg. The new design includes a smaller barrel which helps reduce weight and minimises vibration and subsequent damaged caused by driving on corrugated roads found in remote and harsh environments.

Features:

- Streamline in design and light in weight
- SMA-Male connector
- Ruggedized construction for extreme conditions.
- Can be mounted to car bonnet or bulbar



Electrical Specifications		
Frequency Range	698-960 MHz	1710-2170 MHz
Gain	4 dBi	5 dBi
VSWR	≤2.0	≤2.0
Polarization	Vertical	
Horizontal Beamwidth	360°	
Vertical Beamwidth	48°	29°
Input Impedance	50 Ω	
Max.Power	50 W	
Lightning Protection	DC Ground	
Mechanical Specifications		
Connector	SMA-Male with 4.5m Coax Cable	
Dimensions	Ø16x600 mm	
Weight	1.2 kg	
Reflector Material	Copper	
Radome Material	Fiberglass	
Antenna Color	Black / White	
Operating Temperature	-40°C to +65 °C	
Mounting Pole	Ø38-Ø52 mm	